



摇臂钻床
RADIAL DRILLING MACHINE

沈阳俊诚智能装备技术有限公司

- ◆ 80 years of history
- ◆ Easy and fast operation
- ◆ Traditional craft
- ◆ Worry-free service nationwide



技术参数

Item	Unit	Z3080 × 25	Z3050X16/1	Z3040X13/2	Z3032X10/1	Z3032X8/1	Z3732X8
Max. Drilling Dia.	mm	80	50	40	32	32	32
Distance between spindle axis and column	Max.	mm	2500	1600	1300	1000	820
	Min.	mm	500	350	300	300	325
Distance between spindle nose and working surface of machine base	Max.	mm	2000	1220	1120	1000	850
	Min.	mm	550	320	300	220	90
Spindle travel	mm	450	315	280	280	240	130
Spindle taper	No.	6#	5#	4#	4#	4#	4#
Spindle speed range	r/min	16–1250	25–2000	32–2500	32–2500	75–1220	63–860
Spindle speed level	级	16	16	16	16	6	6
Spindle feed range	mm	0.04–3.2	0.04–3.2	0.10–1.25	0.10–1.25	0.10–0.25	0.07–0.22
Spindle feed level	级	16	16	8	8	3	4
Worktable size	mm	1000x800x560	500x500x630	550x450x450	550x450x450	400x400x350	
Headstock travel	mm	2000	1250	1000	700	500	500
Max. spindle torque	Nm	35000	500	250	200	200	100
Main motor power	kW	7.5	4	3	2.2	1.5	1.5
Lifting distance of swing arm	mm	1000	580	540	500	510	730
Machine weight	kg	11000	3500	2500	1600	1200	900
Machine overall dimensions (length X width X height)	mm	3730x1400x3790	2500x1070x2840	2100x900x2310	1760x800x2050	1417x720x1885	1658x720x1910
Machine packaging size (length X width X height)	mm	3820x1630x1700	2690x1190x2570	2320x1050x2550	1970x950x2280	1640x860x2150	1850x880x2130

注：2型除主轴加强外，其余参数与1型完全相同