



www.sande.cl

SANDE S.A.



600 600 0900

FRESADORA UNIVERSAL ISO50 (H)/ ISO40 (V)

SERIE STERK XW6136



Spindle taper	ISO50(H), ISO40(V)
Distance between spindle nose and table surface	0-400mm
Range of spindle speed	60-1800rpm, 12 steps
Swivel angle of table	45°
Table size	1600mm×360mm
Table travel	1000mm×340mm×400mm
Feed speed of table, X/Y/Z	30-680mm/min, max. 2100mm/min
T-slot	3/18/80mm
Main motor	4KW
Motor of rapid feed	1.5KW
Coolant motor	90W
Dimension	2000×2050×2000mm
Machine weight	2400/2600KG



SKAND
BEST INDUSTRIAL OEMS





SANDE S.A.



Accesorios incluidos

Porta fresa , porta broca , tornillo máquina 125mm, kit sistema sujeción piezas, protección husillo,
Lámpara , Lector Digital 3 ejes (DRO) Manual de instrucciones.

Sistema refrigeración de corte

Porta ejes de 22mm y 27mm , con su soporte



Divisor Universal , Código : DH-BS2



Cabezal escopleador , Código : SH-XW



SKAND
BEST INDUSTRIAL OEMS

